

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Calex

**Supplier's address:** Electro Cirkel Retail BV - Public, Lyonstraat 29, 3047 AJ Rotterdam, the Netherlands

**Model identifier:** 2101004000

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	11	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 100
On-mode power ( $P_{on}$ ), expressed in W	10,5	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate con-	Height	298	Spectral power distribution in the
	Width	200	
	Depth	200	
			See image in last page


trol gear, lighting control parts and non-lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	Yes		If yes, equivalent power (W)	79
			Chromaticity coordinates (x and y)	0,527 0,413
<b>Parameters for LED and OLED light sources:</b>				
R9 colour rendering index value	9		Survival factor	1,00
the lumen maintenance factor	0,00			
<b>Parameters for LED and OLED mains light sources:</b>				
displacement factor (cos $\phi_1$ )	0,90		Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	.. <sup>(b)</sup>		If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0		Stroboscopic effect metric (SVM)	0,4

(a) : not applicable;

(b) : not applicable;



Model placed on the Union market from 25/07/2022



**EPREL registration number:** 1253299

<https://eprel.ec.europa.eu/qr/1253299>

**Supplier:** Electro-Cirkel Retail B.V. (Manufacturer)

**Website:** [www.calex.eu](http://www.calex.eu)

**Customer care service:**

**Name:** Electro Cirkel Retail BV - Public

**Website:** [www.calex.eu](http://www.calex.eu)

**Email:** [info@calex.eu](mailto:info@calex.eu)

**Phone:** +31 (0)10 298 19 80

**Address:**

Lyonstraat 29, 3047 AJ Rotterdam, the Netherlands